

Securing technology for you











Table of Contents





03.6

Astragal Mortise Lock & Flushbolts

• AML

Astragal Mortise Lock	03.6. 5
Driving Rods	03.6. 6
Faceplates	03.6. 7
AML Guides and Strike Cups	03.6. 8
• AMLOC	
Astragal Mortise Lock Off-Center	
Driving Rods	03.6. 11
Faceplates	03.6. 12
AMLOCGuides and Strike Cups	03.6. 13





AML Astragal Mortise Lock

Backset Adjustable for Astragal 12.7 - 28mm









Astragal Mortise Lock			
Description	Color	PU	Part Number
Mortise lock (AML)	Zinc	10	6-C7250-19-0-0
	* = Color	PU = Pa	ckaging Unit


- Used on the inactive panel of double doors
- Shoot extends to 25mm (adjustable by reducing rod length)
- Non-handed mechanism
- 20mm faceplate cover with radius ends
- Backset adjustable for astragal thickness 12.7mm to 28mm
- Use with 10mm round rods
- Refer to installation drawing " AML 6-C7250-19-0-0 Cut-Out"
- AML fastening screws are not included. Sizing is dependent on astragal thickness

Driving Rods

for AML Mortise Lock







Top and Bottom Round Rods For AML				
Description	Color	PU	Part Number	
Top rods fixed size				
641mm (25 1/4") long for door slab 79"	Zinc	10	9-C5212-00-0-3	
1047mm (41 1/4") long for door slab 95"	Zinc	10	9-C5214-00-0-3	
Additional Top rods				
1619mm (63 3/4") long	Zinc	10	9-U1015-00-0-3	
Bottom rod fixed size – Mortise lock height 1280mm				
1200mm (47 1/4") long	Zinc	10	9-U1010-00-0-3	
	* = Color	PU = P	ackaging Unit	


- Made of zinc plated steel
- Ø 10mm rods with beveled tip
- Can be cut to size
- Use with astragal mortise lock (6-C7250-19-0-0)
- For panels up to 117 in, we recommend using rod 9-U1010-00-0-3 for the bottom of the door panel. The center of AML will be 1280mm from the bottom of the door panel
- For 10 ft panels (between 117 in and 121 in), use rod 9-U1015-00-0-3 for the bottom rod and cut at 1300mm. The center of AML will be 1380mm from the bottom of the door panel
- For the top rod length, measure the center of the AML to the top of the door panel and subtract 80mm. You may have to recut the rod to fit your door height

Faceplate

Astragal Mortise Lock Faceplate Covers







Mortise Lock Faceplate Cover			
Description	Color	PU	Part Number
Faceplate for Mortise Lock	Dark Bronze PC	50	6-C7260-00-0-5
	Black PC	50	6-C7260-00-0-6
	Stainless Steel	50	6-C7260-00-0-8B
	* = Color	PU = Pa	ckaging Unit
5	6 8B		

- 20mm Faceplate cover made of stainless steel 304
- Use with astragal mortise lock (6-C7250-19-0-0)
- Supplied with installation screws



Faceplate screws			
Description	Color	PU	Part Number
M5 x10 mm Screw	Dark Bronze PC	1000	9-C5129-10-0-5
	Black PC	1000	9-C5129-10-0-6
	Stainless Steel	1000	9-C5129-10-0-8B
	* = Color	PU = Pa	ckaging Unit
5	6 8B		

AML Guides & Strike Cups








Reinforcement strip and guide for top and bottom door edges			
Description	Color	PU	Part Number
Guide	SS	1	9-C4310-00-0-8B
	* = Color	PU = Pa	ckaging Unit

Additional information

- Made of stainless steel
- Reinforces the shoot bolts for higher performance
- No fastening screws included
- 82.5mm x 18.5mm



Reinforcing Strip 20mm			
Description	Color	PU	Part Number
Reinforcing strip for shoot bolts	Stainless Steel	1	9-C4316-00-0-8B
	* = Color	PU = Pa	ckaging Unit

- Made of stainless steel
- Reinforced the edges of shoot bolts for higher performance
- No fastening screws included
- 200mm x 20mm



AML keeper			
Description	Color	PU	Part Number
Keeper 52mm	Stainless Steel	1	9-C4308-00-K-8B
* = Color PU = Packaging Unit		ckaging Unit	

AML Guides & Strike Cups








Fastening Screws			
Description	Color	PU	Part Number
D1 screws	Stainless Steel	1000	9-C5362-32-0-8
	* = Color	PU = Pa	ckaging Unit

Additional information

- Stainless steel lock fastening screws 32mm
- Type D1 with self-drilling spiral point and high duplex thread with "Quadrex" socket
- Sharp tip for quick drive





AML Guide for Top and Bottom round rods and shootbolt			
Description Color PU Part Number			
Guide	Black	1	9-C0540-00-0-0
* = Color PU = Packaging Unit			





Adjustable Strike Cups 22mm and 27mm Deep			
Description	Color	PU	Part Number
22mm sleeve for shoot bolts	Black	100	9-C4306-22-0-0
27mm sleeve for shoot bolts	Black	100	9-C4306-27-0-0
* = Color PU = Packaging Unit			


- Made of reinforced nylon
- In and out adjustment of 1mm
- Allows a lateral adjustment of ±2.8mm
- Possible pull in of 5mm
- For Ø 10mm round shootbolts


AMLOC Astragal Mortise Lock Off-Center

With off-centered drive rods









Astragal Mortise Lock with Off-centered drive rods			
Description	Color	PU	Part Number
AMLOC	Zinc	10	6-C7252-19-0-0
* = Color PU = Packaging Unit		ackaging Unit	


- Used on the inactive panel of double doors
- Shoot extends to 25mm (adjustable by reducing rod length)
- Non-handed mechanism
- 20mm faceplate cover with radius end
- Self-adjusting drive rod connectors for astragal 12.7mm to 28mm
- Use with off-centered rods
- Can be used with one depth (See installation drawing D-2017-002-01)
- Fastening screws are not included.
 Fastening screws can be fastened through the AMLOC into the door slab

Driving Rods

for Off-Centered Mortise Lock







Rods for AMLOC				
Description	Color	PU	Part Number	
Top fixed rod size off-centered				
647mm (25 1/2") long for door slab 79"	SS	10	6-C4400-06-0-1	
1053mm (41 1/2") long for door slab 95"	SS	10	6-C4400-10-0-1	
Bottom rod off-centered				
1200mm (47 1/4") long for door slab 79" and 95"	SS	10	6-C4400-12-0-1	
	* = Color	PU = Pa	ackaging Unit	


- 10mm shoot-boolts made of stainless steel
- Ø 10mm shoot-bolts with beveled tip
- Steel flat drive rods can be easily cut to size
- Use only with AMLOC (6-C7252-19-0-0)

Faceplate

Astragal Mortise lock faceplate covers







Mortise Lock Faceplate				
Description	Color	PU	Part Number	
Faceplate for Mortise Lock	Dark Bronze PC	50	6-C7260-00-0-5	
	Black PC	50	6-C7260-00-0-6	
	Stainless Steel	50	6-C7260-00-0-8B	
	* = Color PU = Packaging Unit		ckaging Unit	



- 20mm Faceplate cover made of stainless steel 304
- Use with astragal mortise lock (6-C7252-19-0-0)
- Supplied with installations screws

AMLOC Guides & Strike Cups








Reinforcement strip and guide for top and bottom door edges				
Description Color PU Part Number				
Guide	SS	1	9-C4310-00-0-8B	
	* = Color	PU = Pa	ckaging Unit	

Additional information


- Made of stainless steel
- Reinforces the shoot bolts for higher performance
- No fastening screws included
- 82.5mm x 18.5mm



Reinforcing Strip 16mm				
Description	Color	PU	Part Number	
Reinforcing strip for shoot bolts	Stainless Steel	1	9-C4315-00-0-8B	
	* = Color	PU = Pa	ckaging Unit	

Additional information

- Made of stainless steel
- Reinforced the edges of shoot bolts for higher performance
- Recommended for PVC and aluminum
- No fastening screws included
- 200mm x 16mm



Reinforcing Strip 20mm				
Description	Color	PU	Part Number	
Reinforcing strip for shoot bolts	Stainless Steel	1	9-C4316-00-0-8B	
	* = Color	PU = Pa	ckaging Unit	

- Made of stainless steel
- Reinforced the edges of shoot bolts for higher performance
- Recommended for timber
- No fastening screws included
- 200mm x 20mm

AMLOC Guides & Strike Cups








Fastening Screws			
Description	Color	PU	Part Number
D1 screws	Stainless Steel	1000	9-C5362-32-0-8
	* = Color	PU = Pa	ckaging Unit

Additional information


- Stainless steel lock fastening screws 32mm
- Type D1 with self-drilling spiral point and high duplex thread with "Quadrex" socket
- Sharp tip for quick drive



AMLOC Middle Guide for Drive Rods				
Description	Color	PU	Part Number	
Middle Guide	Black	1	9-C0550-00-0-6	
	* = Color	PU = Packaging Unit		

Additional information

■ Will support and guide flat drive rod



AMLOC Guide for Top and Bottom stainless 10 mm shoot-bolts				
Description	Color	PU	Part Number	
Guide	Black	1	9-C0541-00-0-6	
	* = Color	PU = Pa	ckaging Unit	

AMLOC Guides & Strike Cups









Adjustable Strike Cups 22 and 27mm Deep				
Description	Color	PU	Part Number	
22mm sleeve for shoot bolts	Black	100	9-C4306-22-0-0	
27mm sleeve for shoot bolts	Black	100	9-C4306-27-0-0	
* = Color PU = Packaging Unit			ckaging Unit	

- Made of reinforced nylon
- In and out adjustment of 1mm
- Allows a lateral adjustment of ±2.8mm
- Possible pull in of 5mm
- For Ø 10mm round shootbolts

Flushbolts










Flush Bolt			
Description	Color	PU	Part Number
Spring Shoot Bolt 200 x 20mm	Zinc	100	6-C4308-20-0-1
Spring Shoot Bolt 200 x 20mm	Black	100	6-C4308-20-0-6
	* = Color	PU = Pa	ckaging Unit

- Used on the inactive panel of double doors
- Shoot projection 16.5mm
- Zinc plated steel
- Easy operation with slider button
- Leaf spring secures lock at locked position
- Dimensions: 200mm x 20mm x 12,5mm
- Refer to installation drawing "D-2019-011-01"



Shoot bolt Strike plate			
Description	Color	PU	Part Number
Strike plate	Stainless Steel	100	6-UK2212-AB-0-SS
	* = Color	PU = Pa	ackaging Unit

Wood Mount Display

for Astragal Mortise Lock





Wood Mount Display with Astragal Mortise Lock			
Description PU Pa			Part Number
AML Wood mount display		1	6-C9620-00-0-9
	* = Color PU = Packaging Unit		nckaging Unit


<u>03</u>

Wood Mount Display

for Off-Centered Astragal Mortise Lock







Wood Mount Display with Off-centered Astragal Mortise Lock			
Description	PU	Part Number	
AMLOC Wood mount display	1	6-C9620-01-0-9	
* = Color	PU = Pa	PU = Packaging Unit	

QUÉBEC / MARITIMES

Ferco Ferrures de Bâtiment Inc. 2000, Rue Berlier Laval, QC H7L 4S4 Canada

T 450 973-1437 1 800 355-8810 F 450 973-7661 ferco@ferco.ca

ONTARIO / WESTERN PROVINCES

Ferco Architectural Hardware Inc. T 905 282-9588 1 800 668-5310 F 905 282-9915

UNITED STATES

Ferco Architectural Hardware Inc. T 1 800 927-1097 F 1 888 454-0161

Edition 01.2022 | Printed in Canada

www.ferco.ca





